



# PETRA DIESEL POWER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 06/28/2022

Version: 1.1

Supersedes: 2015

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product Form : Mixture  
Trade Name : PETRA 3001  
Product code : PETRA DIESEL POWER 12 FL.OZ.  
Other Means of Identification : This diesel fuel additive complies with federal low sulfur content requirements for use in diesel motor vehicles and nonroad engines.

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Fuel Additive

#### 1.3. Details of the supplier of the safety data sheet

Petra Automotive Products  
11085 Regency Green Dr.  
Cypress, TX 77429  
T 713-856-5700

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Flammable liquids Category 4 H227 Combustible liquid  
Carcinogenicity Category 1B H350 May cause cancer  
Aspiration hazard Category 1 H304 May be fatal if swallowed and enters airways

Full text of H- and EUH-statements: see section 16

#### 2.2. Label elements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H227 - Combustible liquid  
H304 - May be fatal if swallowed and enters airways  
H350 - May cause cancer

Precautionary statements (GHS US) :

P201 - Obtain special instructions  
P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection  
P301+P310 - If swallowed: Immediately call a poison control center, doctor, physician,  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P331 - Do NOT induce vomiting.  
P370+P378 - In case of fire: See Section 5.1 Extinguishing Media  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

#### 2.3. Other hazards

Other hazards which do not result in classification : None under normal conditions.

#### 2.4. Unknown acute toxicity (GHS US)

No data available

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Distillates (Petroleum), Hydrotreated Light	(CAS-No.) 64742-47-8	50 – 70	Asp. Tox. 1, H304

# PETRA DIESEL POWER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
2-Ethylhexyl Nitrate	(CAS-No.) 27247-96-7	10.5 – 21	Flam. Liq. 4, H227
Solvent Naphtha (Petroleum), Heavy Aromatic	(CAS-No.) 64742-94-5	3.5 – 7	Asp. Tox. 1, H304
Solvent Naphtha (Petroleum), Light Aromatic	(CAS-No.) 64742-95-6	1.75 – 5.25	Flam. Liq. 2, H225 Carc. 1B, H350 Asp. Tox. 1, H304
2-Ethyl-1-Hexanol	(CAS-No.) 104-76-7	1.75 – 5.25	Flam. Liq. 4, H227
1, 2, 4 Trimethylbenzene	(CAS-No.) 95-63-6	< 1.75	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Trimethylbenzenes	(CAS-No.) 25551-13-7	0.35 – 1.75	Flam. Liq. 3, H226
Naphthalene	(CAS-No.) 91-20-3	0.35 – 1.75	Acute Tox. 4 (Oral), H302 Carc. 2, H351
Xylene, Mixture of Isomers	(CAS-No.) 1330-20-7	< 0.7	Flam. Liq. 3, H226 Skin Irrit. 2, H315
Cumene	(CAS-No.) 98-82-8	< 0.175	Flam. Liq. 3, H226 Carc. 2, H351 STOT SE 3, H335 Asp. Tox. 1, H304
Mesitylene	(CAS-No.) 108-67-8	< 0.07	Flam. Liq. 3, H226 STOT SE 3, H335
Ethylbenzene	(CAS-No.) 100-41-4	< 0.07	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Allow affected person to breathe fresh air. Allow the victim to rest.
- First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : May cause cancer.
- Symptoms/effects after ingestion : May be fatal if swallowed and enters airways.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Combustible liquid.
- Explosion hazard : May form flammable/explosive vapor-air mixture.

### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

#### 6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Safety glasses.
- Emergency procedures : Evacuate unnecessary personnel.

# PETRA DIESEL POWER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.  
Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

- For containment : Plug the leak, cut off the supply. Dam up the liquid spill. Contain released product, collect/pump into suitable containers.  
Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Keep away from heat, sparks, open flames, hot surfaces. - No smoking.  
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Obtain special instructions. Do not handle until all safety precautions have been read and understood.  
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Always wash hands after handling the product. Keep container tightly closed. Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling. Take off immediately all contaminated clothing and wash it before reuse. Observe normal hygiene standards. Wash contaminated clothing before reuse. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed.  
Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Keep in fireproof place.  
Incompatible products : Strong bases. Strong acids.  
Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

### 7.3. Specific end use(s)

Follow Label Directions.

# PETRA DIESEL POWER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

<b>PETRA DIESEL POWER 12 FL.OZ.</b>	
No additional information available	
<b>2-Ethylhexyl Nitrate (27247-96-7)</b>	
No additional information available	
<b>Solvent Naphtha (Petroleum), Heavy Aromatic (64742-94-5)</b>	
No additional information available	
<b>Solvent Naphtha (Petroleum), Light Aromatic (64742-95-6)</b>	
No additional information available	
<b>bvf dew323w32 (95-63-6)</b>	
No additional information available	
<b>2-Ethyl-1-Hexanol (104-76-7)</b>	
No additional information available	
<b>Trimethylbenzenes (25551-13-7)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA [ppm]	25 ppm
<b>Xylene, Mixture of Isomers (1330-20-7)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA [ppm]	100 ppm
ACGIH OEL STEL [ppm]	150 ppm
<b>Cumene (98-82-8)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA [ppm]	5 ppm
<b>Mesitylene (108-67-8)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA [ppm]	25 ppm
<b>Naphthalene (91-20-3)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA [ppm]	10 ppm
<b>Ethylbenzene (100-41-4)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA [ppm]	20 ppm
<b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA [ppm]	200 ppm 8 Hours
<b>USA - NIOSH - Occupational Exposure Limits</b>	
NIOSH REL (TWA)	100 mg/m <sup>3</sup>

#### 8.2. Appropriate engineering controls

Appropriate engineering controls : Local exhaust ventilation, vent hoods . Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

#### 8.3. Individual protection measures/Personal protective equipment

##### Personal protective equipment:

Gloves. Safety glasses. Avoid all unnecessary exposure.

##### Materials for protective clothing:

Excellent resistance:

##### Hand protection:

Wear protective gloves

##### Eye protection:

Chemical goggles or safety glasses

##### Skin and body protection:

Wear suitable protective clothing

# PETRA DIESEL POWER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Respiratory protection:

Wear respiratory protection.

### Personal protective equipment symbol(s):



### Other information:

Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Light amber to amber.
Odor	: Aromatic . Petroleum-like odour.
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 75 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.853
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Combustible liquid. May form flammable/explosive vapor-air mixture.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide. May release flammable gases.

# PETRA DIESEL POWER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

<b>2-Ethylhexyl Nitrate (27247-96-7)</b>	
LD50 oral rat	> 9600 mg/kg (Rat, Male / female, Experimental value, (maximum achievable concentration), Oral (repeated exposure), 14 day(s))
<b>bvf dew323w32 (95-63-6)</b>	
LD50 oral rat	6000 mg/kg body weight (EU Method B.1 tris: Acute oral toxic – Acute toxic class method, Rat, Male, Experimental value, Oral, 014 day(s))
LD50 dermal rat	3440 mg/kg (24 h, Rat, Male / female, Read-across, Dermal)
ATE US (oral)	6000 mg/kg body weight
ATE US (dermal)	3440 mg/kg body weight
ATE US (vapors)	11 mg/l/4h
<b>Xylene, Mixture of Isomers (1330-20-7)</b>	
LD50 oral rat	> 4000 mg/kg body weight (Equivalent or similar to EU Method B.1, Rat, Female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 4200 mg/kg (Rabbit; Experimental value,Rabbit; Experimental value)
LC50 Inhalation - Rat	29.09 mg/l (Equivalent or similar to EU Method B.2, 4 h, Rat, Male, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (vapors)	29.09 mg/l/4h
ATE US (dust, mist)	29.09 mg/l/4h
<b>Cumene (98-82-8)</b>	
LD50 oral rat	2700 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 014 day(s))
LD50 dermal rabbit	> 3160 mg/kg body weight (24 h, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	39 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	2700 mg/kg body weight
ATE US (vapors)	39 mg/l/4h
ATE US (dust, mist)	39 mg/l/4h
<b>Mesitylene (108-67-8)</b>	
LD50 oral rat	6000 mg/kg body weight (Equivalent or similar to EU Method B.1, Rat, Male, Read-across, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg bw/day (24 h, Rat, Male / female, Read-across, Dermal)
ATE US (oral)	6000 mg/kg body weight
<b>Naphthalene (91-20-3)</b>	
LD50 dermal rat	> 16000 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 0.4 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, (maximum achievable concentration), Inhalation (vapours), 14 day(s))
ATE US (oral)	500 mg/kg body weight
<b>Ethylbenzene (100-41-4)</b>	
LD50 oral rat	3500 mg/kg (Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	15433 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	3500 mg/kg body weight
ATE US (dermal)	15433 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	17.8 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
<b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b>	
LD50 oral rat	> 5000 mg/kg body weight
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	> 5.28 mg/l/4h Based on lack of mortality and systemic effects

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Not classified

# PETRA DIESEL POWER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.

<b>Solvent Naphtha (Petroleum), Light Aromatic (64742-95-6)</b>	
IARC group	3 - Not classifiable

<b>Xylene, Mixture of Isomers (1330-20-7)</b>	
IARC group	3 - Not classifiable

<b>Cumene (98-82-8)</b>	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen

<b>Naphthalene (91-20-3)</b>	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

<b>bvf dew323w32 (95-63-6)</b>	
STOT-single exposure	May cause respiratory irritation.

<b>Cumene (98-82-8)</b>	
STOT-single exposure	May cause respiratory irritation.

<b>Mesitylene (108-67-8)</b>	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Not classified

<b>Ethylbenzene (100-41-4)</b>	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : May be fatal if swallowed and enters airways.

Viscosity, kinematic : No data available

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Symptoms/effects : May cause cancer.

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways.

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>2-Ethylhexyl Nitrate (27247-96-7)</b>	
LC50 - Fish [1]	2 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	> 12.6 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	3.22 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)

<b>bvf dew323w32 (95-63-6)</b>	
LC50 - Fish [1]	7.72 mg/l (96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)

<b>2-Ethyl-1-Hexanol (104-76-7)</b>	
LC50 - Fish [1]	17.1 mg/l (EU Method C.1, 96 h, Leuciscus idus, Flow-through system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	39 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	16.6 mg/l (EU Method C.3, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, GLP)

<b>Trimethylbenzenes (25551-13-7)</b>	
LC50 - Fish [1]	2.72 – 13 mg/l (96 h, Pisces)

<b>Xylene, Mixture of Isomers (1330-20-7)</b>	
LC50 - Fish [1]	2.6 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static renewal, Fresh water, Read-across, Lethal)



# PETRA DIESEL POWER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Xylene, Mixture of Isomers (1330-20-7)</b>	
ErC50 algae	4.36 mg/l (OECD 201: Alga, Growth Inhibition Test, 73 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
<b>Cumene (98-82-8)</b>	
LC50 - Fish [1]	4.8 mg/l (EPA OTS 797.1400, 96 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	2.14 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	2.01 mg/l (EU Method C.3, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, GLP)
<b>Mesitylene (108-67-8)</b>	
LC50 - Fish [1]	12.52 mg/l (96 h, Carassius auratus, Flow-through system, Fresh water, Experimental value, Nominal concentration)
ErC50 algae	53 mg/l (DIN 38412-9, 48 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)
<b>Naphthalene (91-20-3)</b>	
LC50 - Fish [1]	0.96 ppm (Oncorhynchus gorboscha, Flow-through system, Salt water, Experimental value, Lethal)
EC50 - Crustacea [1]	2.16 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
<b>Ethylbenzene (100-41-4)</b>	
LC50 - Fish [1]	5.1 mg/l (ASTM, 96 h, Menidia menidia, Flow-through system, Salt water, Experimental value, Lethal)
EC50 - Crustacea [1]	1.8 – 2.4 mg/l (US EPA, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)

### 12.2. Persistence and degradability

<b>PETRA DIESEL POWER 12 FL.OZ.</b>	
Persistence and degradability	Not established.
<b>2-Ethylhexyl Nitrate (27247-96-7)</b>	
Persistence and degradability	Not readily biodegradable in water.
<b>Solvent Naphtha (Petroleum), Heavy Aromatic (64742-94-5)</b>	
Persistence and degradability	Not established.
<b>bvf dew323w32 (95-63-6)</b>	
Persistence and degradability	Not readily biodegradable in water. Not established.
Chemical oxygen demand (COD)	0.44 g O <sub>2</sub> /g substance
<b>2-Ethyl-1-Hexanol (104-76-7)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil. Not established.
<b>Trimethylbenzenes (25551-13-7)</b>	
Persistence and degradability	Biodegradable in the soil. Not readily biodegradable in water.
<b>Xylene, Mixture of Isomers (1330-20-7)</b>	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
<b>Cumene (98-82-8)</b>	
Persistence and degradability	Not readily biodegradable in water. Not established.
Biochemical oxygen demand (BOD)	1.28 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.42 g O <sub>2</sub> /g substance
ThOD	3.2 g O <sub>2</sub> /g substance
<b>Mesitylene (108-67-8)</b>	
Persistence and degradability	Biodegradable in the soil. Biodegradable in water. Not established.
Biochemical oxygen demand (BOD)	0.0957 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	0.319 g O <sub>2</sub> /g substance
ThOD	3.19 g O <sub>2</sub> /g substance
<b>Naphthalene (91-20-3)</b>	
Persistence and degradability	Readily biodegradable in water. Forming sediments in water. Biodegradable in the soil. Adsorbs into the soil. Photolysis in the air. Not established.
Biochemical oxygen demand (BOD)	0 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	0.22 g O <sub>2</sub> /g substance
ThOD	2.99 g O <sub>2</sub> /g substance



# PETRA DIESEL POWER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Ethylbenzene (100-41-4)</b>	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water. Not established.
Biochemical oxygen demand (BOD)	1.44 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.1 g O <sub>2</sub> /g substance
ThOD	3.17 g O <sub>2</sub> /g substance

<b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b>	
Persistence and degradability	Not established.

### 12.3. Bioaccumulative potential

<b>PETRA DIESEL POWER 12 FL.OZ.</b>	
Bioaccumulative potential	Not established.

<b>2-Ethylhexyl Nitrate (27247-96-7)</b>	
BCF - Fish [1]	1332 l/kg (OECD 305: Bioconcentration: Flow-Through Fish Test, Pisces, QSAR)
Partition coefficient n-octanol/water (Log Pow)	5.24 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C)
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5).

<b>Solvent Naphtha (Petroleum), Heavy Aromatic (64742-94-5)</b>	
Bioaccumulative potential	Not established.

<b>Solvent Naphtha (Petroleum), Light Aromatic (64742-95-6)</b>	
Partition coefficient n-octanol/water (Log Pow)	2.1 – 6

<b>bvf dew323w32 (95-63-6)</b>	
BCF - Fish [1]	243 (Pimephales promelas, QSAR)
Partition coefficient n-octanol/water (Log Pow)	3.63 (Experimental value, KOWWIN)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4). Not established.

<b>2-Ethyl-1-Hexanol (104-76-7)</b>	
Partition coefficient n-octanol/water (Log Pow)	2.9 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4). Not established.

<b>Trimethylbenzenes (25551-13-7)</b>	
BCF - Fish [1]	23 – 342 (Cyprinus carpio)
Partition coefficient n-octanol/water (Log Pow)	3.42 – 4.13 (Experimental value)
Bioaccumulative potential	Potential for bioaccumulation (4 ≤ Log Kow ≤ 5).

<b>Xylene, Mixture of Isomers (1330-20-7)</b>	
BCF - Fish [1]	7.2 – 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Read-across)
Partition coefficient n-octanol/water (Log Pow)	3.2 (Read-across, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

<b>Cumene (98-82-8)</b>	
BCF - Other aquatic organisms [1]	94.69 l/kg (BCFBAF v3.00, Calculated value)
Partition coefficient n-octanol/water (Log Pow)	3.55 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 23 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4). Not established.

<b>Mesitylene (108-67-8)</b>	
BCF - Fish [1]	161 (Pimephales promelas, QSAR)
Partition coefficient n-octanol/water (Log Pow)	3.42 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500). Not established.

<b>Naphthalene (91-20-3)</b>	
BCF - Fish [1]	23 – 168 (OECD 305: Bioconcentration: Flow-Through Fish Test, 8 week(s), Cyprinus carpio, Flow-through system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	3.4 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500). Not established.

<b>Ethylbenzene (100-41-4)</b>	
BCF - Fish [1]	1 (6 week(s), Oncorhynchus kisutch, Flow-through system, Salt water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	3.6 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500). Not established.

<b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b>	
Bioaccumulative potential	Not established.

### 12.4. Mobility in soil

# PETRA DIESEL POWER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>2-Ethylhexyl Nitrate (27247-96-7)</b>	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.75 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Ecology - soil	Low potential for mobility in soil.
<b>bvf dew323w32 (95-63-6)</b>	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.04 (log Koc, Calculated value)
Ecology - soil	Low potential for mobility in soil. May be harmful to plant growth, blooming and fruit formation.
<b>2-Ethyl-1-Hexanol (104-76-7)</b>	
Surface tension	47 mN/m (20 °C, 0.81 g/l)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.5475 – 2.1177 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.
<b>Trimethylbenzenes (25551-13-7)</b>	
Ecology - soil	Adsorbs into the soil.
<b>Xylene, Mixture of Isomers (1330-20-7)</b>	
Surface tension	28.01 – 29.76 mN/m (25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)
Ecology - soil	Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation.
<b>Cumene (98-82-8)</b>	
Surface tension	28.2 mN/m (20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.946 (log Koc, Calculated value)
Ecology - soil	Low potential for adsorption in soil.
<b>Mesitylene (108-67-8)</b>	
Surface tension	27550 mN/m (25 °C, 100 vol %)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.87 (log Koc, Calculated value)
Ecology - soil	Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation.
<b>Naphthalene (91-20-3)</b>	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.864 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Low potential for adsorption in soil.
<b>Ethylbenzene (100-41-4)</b>	
Surface tension	71.2 mN/m (23 °C, 0.058 g/l, EU Method A.5: Surface tension)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.71 (log Koc, PCKOCWIN v1.66, QSAR)
Ecology - soil	Low potential for adsorption in soil. Toxic to soil organisms.

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

- Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.
- Additional information : Handle empty containers with care because residual vapors are flammable.
- Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

# PETRA DIESEL POWER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT

Not applicable

#### Transport by sea

#### Air transport

Proper Shipping Name (IATA) : Not Regulated

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

PETRA DIESEL POWER 12 FL.OZ.	
SARA Section 311/312 Hazard Classes	Health hazard - Aspiration hazard
2-Ethylhexyl Nitrate (27247-96-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Solvent Naphtha (Petroleum), Light Aromatic (64742-95-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
bvf dew323w32 (95-63-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
SARA Section 313 - Emission Reporting	1 %
2-Ethyl-1-Hexanol (104-76-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	TP - TP - indicates a substance that is the subject of a proposed TSCA section 4 test rule.
Trimethylbenzenes (25551-13-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Xylene, Mixture of Isomers (1330-20-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	100 lb
SARA Section 311/312 Hazard Classes	Fire hazard
SARA Section 313 - Emission Reporting	1 %
Cumene (98-82-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	5000 lb
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
SARA Section 313 - Emission Reporting	1 %
Mesitylene (108-67-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Naphthalene (91-20-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	100 lb
SARA Section 313 - Emission Reporting	1 %
Distillates (Petroleum), Hydrotreated Light (64742-47-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard

# PETRA DIESEL POWER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 15.2. International regulations

#### CANADA

<b>PETRA DIESEL POWER 12 FL.OZ.</b>	
WHMIS Classification	Class B Division 2 - Flammable Liquid
<b>2-Ethylhexyl Nitrate (27247-96-7)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>Solvent Naphtha (Petroleum), Light Aromatic (64742-95-6)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>bvf dew323w32 (95-63-6)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
<b>2-Ethyl-1-Hexanol (104-76-7)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>Trimethylbenzenes (25551-13-7)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>Xylene, Mixture of Isomers (1330-20-7)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>Cumene (98-82-8)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
<b>Mesitylene (108-67-8)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>Naphthalene (91-20-3)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

#### EU-Regulations

<b>Solvent Naphtha (Petroleum), Light Aromatic (64742-95-6)</b>
<b>bvf dew323w32 (95-63-6)</b>
<b>2-Ethyl-1-Hexanol (104-76-7)</b>
<b>Trimethylbenzenes (25551-13-7)</b>
<b>Xylene, Mixture of Isomers (1330-20-7)</b>
<b>Cumene (98-82-8)</b>
<b>Mesitylene (108-67-8)</b>
<b>Naphthalene (91-20-3)</b>
<b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b>

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

#### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

##### 15.2.2. National regulations

<b>Solvent Naphtha (Petroleum), Light Aromatic (64742-95-6)</b>
<b>bvf dew323w32 (95-63-6)</b>
<b>2-Ethyl-1-Hexanol (104-76-7)</b>
<b>Trimethylbenzenes (25551-13-7)</b>
<b>Xylene, Mixture of Isomers (1330-20-7)</b>
Listed on EPA Hazardous Air Pollutant (HAPS)

# PETRA DIESEL POWER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Cumene (98-82-8)

Listed on IARC (International Agency for Research on Cancer)  
Listed as carcinogen on NTP (National Toxicology Program)  
Listed on EPA Hazardous Air Pollutant (HAPS)

### Mesitylene (108-67-8)

Listed on IARC (International Agency for Research on Cancer)  
Listed as carcinogen on NTP (National Toxicology Program)  
Listed on EPA Hazardous Air Pollutant (HAPS)

### Distillates (Petroleum), Hydrotreated Light (64742-47-8)

## 15.3. US State regulations

### PETRA DIESEL POWER 12 FL.OZ.( )

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S. - California - Proposition 65

### 2-Ethylhexyl Nitrate (27247-96-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

### Solvent Naphtha (Petroleum), Heavy Aromatic (64742-94-5)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

### Solvent Naphtha (Petroleum), Light Aromatic (64742-95-6)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

### bvf dew323w32 (95-63-6)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

### 2-Ethyl-1-Hexanol (104-76-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

### Trimethylbenzenes (25551-13-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

# PETRA DIESEL POWER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Xylene, Mixture of Isomers (1330-20-7)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	
<b>Cumene (98-82-8)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	
<b>Mesitylene (108-67-8)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	
<b>Naphthalene (91-20-3)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	
<b>Ethylbenzene (100-41-4)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	
<b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	
<b>bvf dew323w32 (95-63-6)</b>				
<b>State or local regulations</b>				
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New York City - Right to Know Hazardous Substances List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>2-Ethyl-1-Hexanol (104-76-7)</b>				
<b>State or local regulations</b>				
U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>Trimethylbenzenes (25551-13-7)</b>				
<b>State or local regulations</b>				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New York City - Right to Know Hazardous Substances List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>Xylene, Mixture of Isomers (1330-20-7)</b>				
<b>State or local regulations</b>				
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List				

# PETRA DIESEL POWER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Xylene, Mixture of Isomers (1330-20-7)

U.S. – New York City – Right to Know Hazardous Substances List  
U.S. - Pennsylvania - RTK (Right to Know) List

### Cumene (98-82-8)

#### State or local regulations

U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations  
U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. – New York City – Right to Know Hazardous Substances List  
U.S. - Pennsylvania - RTK (Right to Know) List

### Mesitylene (108-67-8)

#### State or local regulations

U.S. – New York City – Right to Know Hazardous Substances List

### Naphthalene (91-20-3)

#### State or local regulations

U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations  
U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. – New York City – Right to Know Hazardous Substances List  
U.S. - Pennsylvania - RTK (Right to Know) List

### Ethylbenzene (100-41-4)

#### State or local regulations

U.S. - California - Proposition 65

## SECTION 16: Other information

Indication of changes : Revision - See : \*

Other information : None.


Full text of H-phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H350	May cause cancer
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



### Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 2 Moderate Hazard

Physical : 0 Minimal Hazard

Personal protection : B



# PETRA DIESEL POWER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

*The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product*

*Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.*