

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 09/23/2021 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form Mixture

Trade name Petra UltraCool™ EV Coolant

Product code 4018G and 4018G5

1.2. Recommended use and restrictions on use

Recommended use Automotive coolant for hybrid electric vehicles (HEV/PHEV) and battery electric vehicles (BEV).

Pre-diluted 50/50, ready to use, do not add water.

1.3. Supplier

Manufacturer

Petra Automotive Products 11085 Regency Green Dr. Cypress, Texas 77429

Telephone: 888-738-7261

1.4. Emergency telephone number

Emergency number CHEMTREC: (800) 424-9300

1-703-527-3887 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Acute toxicity (oral) Category 4 H302 Harmful if swallowed

Specific target organ toxicity (repeated exposure) Category 2 H373 May cause damage to organs through prolonged or repeated exposure

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)





Signal word (GHS US) : Warning

Hazard statements (GHS US) : H302 - Harmful if swallowed

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) : P260 - Do not breathe mist, spray, vapors.

P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product.

P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.

P314 - Get medical advice/attention if you feel unwell.

P330 - Rinse mouth.

P501 - Dispose in a safe manner in accordance with local/national regulations

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

51.42% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Ethylene glycol	(CAS-No.) 107-21-1	30 – 60	Acute Tox. 4 (Oral), H302 STOT RE 2. H373

09/24/2021 US-OSHA - en Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
Benzotriazole	(CAS-No.) 95-14-7	1 – 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Aquatic Acute 3, H402

Full text of hazard classes and H-statements: see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice.

First-aid measures after inhalation : Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed

by warm water rinse.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness

persists

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and

symptoms

: Harmful if swallowed.

Symptoms/effects : Causes damage to organs.

Symptoms/effects after ingestion : Swallowing a small quantity of this material will result in serious health hazard.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

No additional information available

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect

spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

09/24/2021 US-OSHA - en 2/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation

of vapor. Avoid breathing mist, spray, vapors.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands, forearms and face thoroughly

after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well-ventilated place. Keep container closed when

not in use.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

Maximum storage period : 1 year After the one year storage period has elapsed, the applicability should be tested by

measuring electrical conductivity and pH.

Storage temperature : ≤ 30 °C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

EV Coolant SLC

No additional information available

Ethylene glycol (107-21-1)

No additional information available

Benzotriazole (95-14-7)

No additional information available

8.2. Appropriate engineering controls

No additional information available

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Materials for protective clothing:

Work clothes protecting arms, legs and body

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of inadequate ventilation wear respiratory protection.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : Colorless to faint yellow

Odor : slight

Odor threshold : No data available

09/24/2021 US-OSHA - en 3/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

pH : 5.84

Melting point : No data available

Freezing point : -41 °C
Boiling point : 115 °C

: No data available Flash point : No data available Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) : Non flammable. Vapor pressure : No data available : No data available Relative vapor density at 20 °C : 1.074 g/ml Relative density Solubility : Water: 100 % Partition coefficient n-octanol/water (Log Pow) : No data available : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic **Explosion limits** : No data available

: No data available

: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Explosive properties
Oxidizing properties

No additional information available

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

Stable under normal conditions of use.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Ethylene glycol (107-21-1)	
Unknown acute toxicity (GHS US)	51.42% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))
ATE US (oral)	939.713 mg/kg body weight

Ethylene glycol (107-21-1)		
	LD50 oral rat	4700 mg/kg
	LD50 dermal rat	10600 mg/kg
	Benzotriazole (95-14-7)	
- 1	155	"

Benzotriazole (95-14-7)	
LD50 oral rat	560 mg/kg
LD50 dermal rabbit	> 10000 mg/kg
LC50 Inhalation - Rat	1910 mg/m³ (Exposure time: 3 h)

09/24/2021 US-OSHA - en 4/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin corrosion/irritation : Not classified

pH: 5.84

Serious eye damage/irritation : Not classified

pH: 5.84

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Ethylene glycol (107-21-1)

STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified
Viscosity, kinematic : No data available

Potential Adverse human health effects and

symptoms

: Harmful if swallowed.

Symptoms/effects : Causes damage to organs.

Symptoms/effects after ingestion : Swallowing a small quantity of this material will result in serious health hazard.

SECTION 12: Ecological information

12.1. Toxicity

Ethylene glycol (107-21-1)	
EC50 Daphnia 1	46300 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	14 – 18 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
NOEC chronic crustacea	4.2 mg/l
Benzotriazole (95-14-7)	
LC50 fish 1	39 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	141.6 mg/l (Exposure time: 48 h - Species: water flea)

12.2. Persistence and degradability

EV Coolant SLC		
	Persistence and degradability	Not established.

12.3. Bioaccumulative potential

EV Coolant SLC	
Bioaccumulative potential	Not established.
Ethylene glycol (107-21-1)	
Partition coefficient n-octanol/water (Log Pow)	-1.93

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose in a safe

manner in accordance with local/national regulations.

09/24/2021 US-OSHA - en 5/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Non Regulated

Transport by sea

Non Regulated

Air transport

Non Regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Ethylene glycol (107-21-1)		
Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS)		
CERCLA RQ	5000 lb	
Benzotriazole (95-14-7)		
EPA TSCA Regulatory Flag	TP - TP - indicates a substance that is the subject of a proposed TSCA section 4 test rule.	

15.2. International regulations

No additional information available

15.3. US State regulations



This product can expose you to Ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information : None.

Full text of H-phrases:

H302	Harmful if swallowed
H332	Harmful if inhaled
H373	May cause damage to organs through prolonged or repeated exposure
H402	Harmful to aquatic life

NFPA health hazard

: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

 0 - Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.

2 0

09/24/2021 US-OSHA - en 6/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection : H

H - Splash goggles, Gloves, Synthetic apron, Vapor respirator

SDS US (GHS HazCom 2012)

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

09/24/2021 US-OSHA - en 7/7