

# Petra 20W-50 Synthetic Blend Engine Oil

PN 1205055/120275 Specification Sheet



## Product Description

Petra 20W-50 Synthetic Blend Engine Oil is specifically formulated as a high-performance viscosity grade oil for diesel and gasoline engines. This product is designed to deliver unmatched performance under severe race operation, air-cooled operating conditions, and in any driving condition, from mild to severe. Its low-temperature properties enable impressive lubrication at low ambient temperatures, helping ensure easy starting, less drain on the start system, and wear protection. This oil also offers outstanding protection in four-cycle and V-twin type engines. It is suitable for all Japanese and North American 4-stroke motorcycles where SAE 20W-50 is recommended.

## Advantages & Uses

- Provides excellent oil flow over a wide temperature range.
- Excellent performance under extremely hot operating conditions helping to minimize deposit formation.
- Excellent lubrication at cold operating conditions helping with easy starting and rapid wear protection.
- Delivers proven wet clutch performance for smooth operation.

## Features

- Helps provide engine cleanliness.
- Wear protection from rust and corrosion.
- Low-temperature properties.
- Enhanced frictional properties.



SAE Grade	20W-50
Cold-Cranking Simulator, Apparent Viscosity @ -15 C, mPa.s, ASTM D5293	7,500
Density @ 15.6 C, g/cm <sup>3</sup> , ASTM D4052	0.87
Flash Point, Pensky-Martens Closed Cup, °C, ASTM D93	214
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	20.8
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	172
Mini-Rotary Viscometer, Apparent Viscosity, -20 C, mPa.s, ASTM D4684	14,000
Pour Point, °C, ASTM D97	-42
Viscosity Index, ASTM D2270	142



11085 Regency Green Drive • Cypress, Texas 77429  
petraautoproducs.com • 1-888-Petra-61 • info@petraautoproducs.com

follow us on:

