

# Petra SAE 75W-90 Synthetic Gear Oil

## PN 89016G (16 gal) Specification Sheet



### Product Description:

Petra Synthetic 75W-90 Gear Oil is premium-quality created specially for transmissions and final drives. It meets the toughest industry specifications for automotive extreme pressure (EP) gear lubricants including limited slip differentials. It was formulated for extreme pressure offset spiral bevel and hypoid gear sets (ring and pinion gears) in heavy-duty trucks, as well as farm, logging, and construction machines.

### Advantages & Uses:

- Greater film strength at higher operating temperatures
- Reduced wear at start up and ease of startup even in artic condidtions
- Meets requirements for API GL-5, MT-1, Limited Slip,
- MIL PRF 2105E
- Mack GO-J Plus
- SAE J2360
- Eaton Roadranger E500
- Scania STO 1:0
- ZF TE-ML 07A/08
- Dana SHAES 429 Rev. A
- DANA SHAES 256 Rev. C
- Meritor 0-76N
- MB-Approval 235.8
- International TMS-6816
- ZF TE-ML 05B/16F/21B
- ZF TE-ML 12B
- Voith Turbo 132.00374401/132.00374402
- U.S. Steel Specification 224

### Features:

- Multi-viscosity for year round use over wide temperature range
- Extreme pressure additives help prevent gear scuffing and scoring
- Helps Prevent formation of rust and sludge throughout the system
- Excellent resistance to foaming
- Extended drain intervals versus conventional products



11085 Regency Green Drive • Cypress, Texas 77429  
www.petraoilco.com • 1-888-Petra-61 • info@petraoilco.com

follow us on:

