

Petra Diesel Fuel Power II

(BULK) 301532 (32 FL OZ) | 3015G (1 gal)
3015G5 (5 gal) | 3015G55 (55 gal)

Technical Data Sheet



Product Description:

Petra Diesel Fuel Power II is a multifunctional middle distillate fuel additive that recovers lost power, increases cetane number, prevents filter plugging, prevents sludging, and cleans injectors in newer model-year vehicles operating high pressure fuel injectors. Through extensive OEM engine testing and commercial application in heavy-duty diesel engine fleets, including on-road vehicle fleets and heavy-duty mining equipment, Diesel Fuel Power II has proven effective in all diesel fuels and biodiesel blends.

Features and Benefits:

Petra Diesel Fuel Power II delivers the following performance benefits in all diesel engines:

- Increases cetane up to 6 numbers
- Reduces cost of maintenance and downtime
- Injector "Clean-up" and "Keep Clean" capabilities
- Prevents fuel soot and sludge formation caused by thermal stressing within the engine, extending fuel filter, injector, lube oil, and fuel pump life
- Restores lost horsepower and fuel economy
- Reduces exhaust emissions and soot generation, thereby reducing DPF regenerations
- Provides thermal and oxidative stability, lubricity, corrosion protection, and water dispersancy

Recommended Treat Rate Range:

- 301532: 32 FL OZ treats 250 gallons (946 L)
- 3015G, 3015G5, 3015G55: 1 gallon (3.785L) treats 1000 gallons (3785 L)

40CFR80.591 Compliance Statement:

The sulfur content of this diesel fuel additive does not exceed 15 ppm. This is a LEGAL DIESEL® Fuel Additive product.



Typical Properties	
Appearance	Clear Yellow Liquid
Specific Gravity, 60/60°F (15.6/15.6°C)	0.963
Density, lb/gal, 60°F, (15.6°C)	8.03
Flash Point, PMCC, °F (°C)	>158 (>70)
Pour Point, °F (°C)	<-40 (<-40)
Viscosity, cSt @ 104°F (40°C)	3



11085 Regency Green Drive • Cypress, Texas 77429
www.petraautoproducs.com • 1-888-Petra-61
info@petraautoproducs.com

follow us on:

